



cluster queue lock message wireless transaction server noncluster OR non-cluster

Search

Advanced Search

Results 1 - 10 of about 118 for cluster queue lock message wireless transaction server noncluster OR non-cluster. (0.47 seconds)[Show options...](#)Did you mean: cluster queue lock message wireless transaction server **non cluster** OR non-cluster

1. [Sun Java Enterprise System Glossary](#)

The CMM ensures that **non-cluster** members cannot corrupt data and A quick reconfiguration of the Distributed Lock Manager is performed to Interpreted as a packaged enterprise application, a **transaction** system, or a user application.

Message Queue message server (n.) Software that provides delivery ...

docs.sun.com/source/816-6873/index.html - [Cached](#) - [Similar](#)

2. [\[PDF\] Oracle Application Server Integration Installation Guide](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Step 6: If Installing on a Cold Failover **Cluster** (CFC) Middle Tier Optimizing **Transaction** Timeout for Oracle BPEL **Server** and short **message** service (SMS) channels, then the **wireless** service settings must The name of the **queue** manager that provides access to the **queues** ...

download.oracle.com/docs/cd/B28095_05/pc.1012/b25760.pdf - [Similar](#)

3. [Database Error Messages](#)

1-6 Oracle9i Database Error **Messages** Part II Oracle Database **Server Messages**

instance Cause: **Cluster** database command issued for **non cluster** database

ORA-01591 lock held by in-doubt distributed **transaction** string Cause: An Action:

If there is no **message queue**, restart the SQL*Net IPA servers ...

www.scribd.com/doc/19282837/Database-Error-Messages - [Cached](#) - [Similar](#)

4. [Mike Kruckenberg: April 2004 Archives](#)

Someone on MySQL Team: When the cache finds a result it will **lock** that result, not everything else. but the standards docs always pronounce it Ess **Queue** Ell.

The MySQL **server** uses the NDB API interface to get data from the **cluster**. ...

wanting to have **non-cluster** environments with data from the **cluster**. ...

JBoss Transactions is the default **transaction** manager for JBoss 5. ... JBoss Mitigates risks and helps customers avoid vendor **lock in**. JBoss Messaging provides a **message** counter for each **queue**. The simplest way to start a JBoss **server cluster** is to start several JBoss instances on the same local ...

www.iboss.org/file-access/default/.../Server.../index.html - Cached - Similar

File Format: PDF/Adobe Acrobat - View as HTML

You need to **lock down** your Exchange cluster to prevent the spread of W32.Blaster.

Worm, the that occurs to Exchange databases and transaction logs. ... While you're at it, make sure that your **server** and **message monitors** are functional—they ...

For example, suppose a mail connector queue fills Server A's hard ...

www.doubletake.com/_.../white-paper-ensuring-high-availability-with-ms-exchange-server.pdf - Similar

File Format: PDF/Adobe Acrobat

Information related to **Message Server Queues** and **Topics** are stored here.

distributes the Web requests even across non-cluster server instances and WAP:

Notification of an alert over the **Wireless** Application Protocol, to mobile phones or

The lock is released only when the transaction completes. ...

www.pramati.com/docstore/1500009/psv50techref.pdf - Similar

File Format: PDF/Adobe Acrobat

[Jump to Starting and Killing All WebLogic Servers in a Domain or Cluster ...](#): To view

the messages as they are being printed to the file. open a command for wireless

applications Note: For non-cluster servers, JMS queue—the transaction will
still Lock WebLogic. Server. LOCK ...

edocs.bea.com/wls/docs70/pdf/adminguide.pdf - Similar

by BEA WebLogic - Related articles - All 49 versions

File Format: PDF/Adobe Acrobat

and transaction size is always a serious problem on UNIX-based systems. This is

server handles all aspects of security and lock management. Non-cluster db

server (for example, UDB ESE). – **Cluster db server** (for example, This flag


reports **message queue** and shared memory segment information. ...

www.redbooks.ibm.com/redbooks/pdfs/sg247071.pdf - Similar
by IBMES Sizing

10. [2.6.23-rc1 short-form changelog \[LWN.net\]](#)

[XFS] Lazy Superblock Counters [XFS] Fix the **transaction** flags to make lazy
linville/wireless-2.6 into upstream kernel/audifilter: kill bogus for SRQ IB/ehca: add
Shared Receive **Queue** support IB/ehca: **Lock** renaming, and nfsd4 gfs2: stop
giving out **non-cluster-coherent** leases Marc Pignat (1): mmc: ...
lwn.net/Articles/242483/ - [Cached](#) - [Similar](#)

Did you mean to search for: [cluster queue lock message wireless transaction server **non cluster** OR non-cluster](#)



[Search within results](#) - [Language Tools](#) - [Search Help](#) - [Dissatisfied? Help us improve](#) - [Try Google Experimental](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [Privacy](#) - [About Google](#)